



The Armor All/STP Products Company

1221 Broadway
Oakland, CA 94612
Tel. (510) 271-7000

Material Safety Data Sheet

I Product:	STP® ENGINE STOP LEAK	139115
Description:	DARK BROWN LIQUID WITH A HYDROCARBON ODOR	
Other Designations	Distributor	Emergency Telephone Nos.
Oil Additive	The Armor All/STP Products Company 1221 Broadway Oakland, CA 94612	For medical emergencies call: (800) 446-1014 For Transportation Emergencies call: (800) 424-9300 (Chemtrec)

II Health Hazard Data	III Hazardous Ingredients		
Eye Irritant. Prolonged skin contact may cause irritation or dermatitis. Vapors or mists may cause respiratory irritation. Swallowing may cause irritation, nausea, vomiting and diarrhea. Aspiration from ingestion may cause lipid pneumonia.	<u>Ingredients</u>	<u>Concentration</u>	<u>Worker Exposure Limit</u>
Individuals with preexisting skin disorders may be at increased risk from exposure to this product.	Mineral Oil	60-100%	5 mg/ m ³ TWA PEL/TLV TWA
Under normal consumer use and conditions, the likelihood of adverse health effects is low.	CAS# Mixture		
FIRST AID:	Petroleum Distillates	5-10%	500 ppm TLV-TWA
EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get immediate medical attention.	CAS# Mixture		
SKIN CONTACT: Remove contaminated clothing. Wash contact area with soap and water. If irritation persists, get medical attention.	Zinc Compounds	1-5%	None established
INGESTION: Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical attention by calling a poison Control or doctor. Never give anything by mouth to an unconscious or drowsy person.	CAS# Proprietary		
INHALATION: If symptoms develop, remove to fresh air. If breathing becomes difficult, give oxygen or administer artificial respiration. Get medical attention if symptoms appear.			
	TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average. PEL = Permissible Exposure Limit		
	None of the ingredients in this product are on the IARC, NTP or OSHA carcinogen list.		

IV Special Protection and Precautions	V Transportation and Regulatory Data
<u>Hygienic Practices:</u> Wash hands thoroughly after contact.	<u>DOT/IMO/IATA:</u> Not Restricted
<u>Engineering Controls:</u> Use local and/or general ventilation to minimize exposure to vapor or mists.	<u>TSCA Status:</u> All ingredients in this product are listed on the TSCA inventory.
<u>Personal Protective Equipment:</u> Wear safety glasses with sideshields. Wear neoprene or nitrile gloves to prevent skin contact. Use a NIOSH-approved respirator if exposure exceeds occupational limits. Keep container closed when not in use.	<u>EPA - SARA Title III/CERCLA:</u> This product is regulated under Sections 311/312. This product contains Zinc compounds (1-5%), which are regulated under Sara 313 and Section 304/CERCLA.
KEEP OUT OF REACH OF CHILDREN	

VI Spill Procedures/Waste Disposal	VII Reactivity Data
<u>Spill Procedures:</u> Wear appropriate protective equipment. Collect with suitable absorbent material and place into a container for disposal. Prevent product from entering sewer or waterways by diking or impounding. Notify National Response Center if spill of any amount enters navigable waters, contiguous zones or adjoining shorelines. Report spills as required under federal, state and local regulations.	<u>Stability:</u> Stable
<u>Waste Disposal:</u> Dispose of in accordance with all applicable federal, state and local regulations.	<u>Hazardous Polymerization:</u> Will not occur.
	<u>Hazardous Decomposition:</u> Carbon monoxide, carbon dioxide and hydrogen sulfide.
	<u>Incompatibilities:</u> Strong oxidizing agents.

VIII Fire and Explosion Data	IX Physical Data
<u>Flash Point:</u> 275°F (CC)	Specific Gravity 0.90 @ 15°C
<u>Fire Extinguishing Agents:</u> Foam, carbon dioxide, dry chemical or water spray (fog). Cool fire exposed containers with water.	Solubility in Water Insoluble
<u>Products of Combustion:</u> Carbon monoxide, carbon dioxide and hydrogen sulfide.	Viscosity 1325 cSt@ 40°C
 133 cSt@ 100°C