

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: 813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 97BR HIGH TACK SUPER ADHESIVE SEALANT 1.75 FL.OZ  
**Item No:** 80060  
**Product Type:** Adhesive/sealant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH TLV: TWA	OSHA PEL:
ACETONE 67-64-1	>40	500 ppm TWA; 750 ppm STEL	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA
ACRYLONITRILE-BUTADIENE POLYMER 9003-18-3	5-15	Not Listed	Not Listed
METHYL ETHYL KETONE (BUTANONE) 78-93-3	<10	200 ppm TWA; 590 mg/m <sup>3</sup> TWA	200 ppm TWA; 590 mg/m <sup>3</sup> TWA
PHENOLIC RESIN 25085-75-0	<10	Not Listed	Not Listed
N-HEXANE 110-54-3	<10	50 ppm TWA	500 ppm TWA; 1800 mg/m <sup>3</sup> TWA
TALC 14807-96-6	<10	2 mg/m <sup>3</sup> respir. dust TWA	20 mppcf TWA
ETHYL ACETATE 141-78-6	<10	400 ppm TWA	400 ppm TWA; 1400 mg/m <sup>3</sup> TWA
SILICON DIOXIDE, AMORPHOUS 112945-52-5	<10	10 mg/m <sup>3</sup> TWA	6 mg/m <sup>3</sup> TWA
4,4 -ISOPROPYLIDENEDIPHENOL 80-05-7	<3	Not Listed	Not Listed
NEOPRENE 9010-98-4	<3	Not Listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** Moderately toxic by ingestion. Ethyl acetate may cause anemia. Prolonged and repeated exposure to methyl ethyl ketone and/or n-hexane may cause peripheral neuropathy by damaging peripheral nerve tissue (that of arms and legs) and result in muscular weakness and loss of sensation. Excessive inhalation causes headache, dizziness, nausea, and incoordination. Long term exposure to high concentrations of vapor may cause lung, liver or kidney damage. May cause eye, skin and respiratory irritation. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss. Note: This product does not contain microcrystalline silica.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. May cause pain, redness or swelling of the eyes and excessive blinking and tear production.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ACETONE 67-64-1	>40	Not known	A4 - Not Classifiable as a Human Carcinogen	Not known
TALC 14807-96-6	<10	male rat-some evidence, female rat-clear evidence, male mice-no evidence, female mice-no evidence	A4- Not classifiable as a human carcinogen	Group 3 Supplement 7, 1987 Monograph 42, 1987
SILICON DIOXIDE, AMORPHOUS 112945-52-5	<10			Amorphous Silica, Group 3: Vol. 68: 1997
4,4 -ISOPROPYLIDENEDIPHENOL 80-05-7	<3	male rat-equivocal; female rat-negative; male mice-negative; female mice-negative		
NEOPRENE 9010-98-4	<3			Group 3 Supplement 7, 1987; Monograph 19, 1979

**Medical Conditions Recognized as Being Aggravated by Exposure:** Persons with preexisting respiratory, liver, kidney, eye or skin diseases may be adversely affected.

#### 4. FIRST AID MEASURES

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. If not breathing, give artificial respiration. Obtain medical attention.

**Skin Contact:** Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### 5. FIRE FIGHTING MEASURES

**Flash Point (°F/C):** <0°F

**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

**Hazardous Products of Combustion:** Oxides of carbon

**Unusual Fire/Explosion Hazards:** Closed containers may rupture or explode when exposed to extreme heat. Keep containers cool. Vapors may travel from container toward sources of ignition and flashback.

**Lower Explosive Limit:** 1.0%

**Upper Explosive Limit:** 13.0%

#### 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

#### 7. HANDLING AND STORAGE

**Storage:** Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

**Handling:** Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. Do not use near heat, sparks or open flame. Keep container closed when not in use. Vapors may accumulate readily and may ignite explosively. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eyes:** Safety glasses with side shields or chemical goggles.

**Skin:** Rubber or plastic gloves.

**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Respiratory Protection:** An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Yellow liquid
<b>Odor:</b>	Ketone odor
<b>Boiling Point:</b>	Not determined.
<b>pH:</b>	Does not apply
<b>Solubility in Water:</b>	Partial
<b>Specific Gravity:</b>	0.91
<b>VOC Content(Wt.%):</b>	18.8% by weight
<b>Vapor Pressure:</b>	400 mm Hg
<b>Vapor Density (Air=1):</b>	2.5
<b>Evaporation Rate:</b>	>1 (air = 1)

## **10. STABILITY AND REACTIVITY**

<b>Chemical Stability:</b>	Stable at normal conditions
<b>Hazardous Polymerization:</b>	WILL NOT OCCUR.
<b>Incompatibilities:</b>	Strong oxidizers
<b>Conditions to Avoid:</b>	Keep away from heat, sparks and open flame
<b>Hazardous Products of Combustion:</b>	Oxides of carbon

## **11. TOXICOLOGICAL INFORMATION**

See Section 3

## **12. ECOLOGICAL INFORMATION**

No data available

## **13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** D001/D035 as per 40CFR 261.21 and a TCLP waste per 261.24 (methyl ethyl ketone and benzene)

## **14. TRANSPORTATION INFORMATION**

### **DOT (49CFR 172)**

#### **Domestic Ground Transport**

<b>DOT Shipping Name:</b>	Consumer Commodity (not more than one liter)
<b>Hazard Class:</b>	ORM-D
<b>UN/ID Number:</b>	None
<b>Marine Pollutant:</b>	None

### **IATA**

<b>Proper Shipping Name:</b>	Consumer Commodity (Not more than 500 ml)
<b>Class or Division:</b>	Class 9
<b>UN/NA Number:</b>	ID 8000

### **IMDG**

<b>Proper Shipping:</b>	Adhesives containing flammable liquid, Limited Quantity
<b>Hazard Class:</b>	Class 3.2
<b>UN Number:</b>	UN 1133

## **15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

METHYL ETHYL KETONE, N-HEXANE

### **CALIFORNIA PROP 65:**

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### **TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

**Product Name:** 97BR HIGH TACK SUPER ADHESIVE  
SEALANT 1.75 FL.OZ

**Item No:** 80060

## **16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 3, REACTIVITY 0

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Health and Safety Manager  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** March/01/2007  
**Revision Number:** 3