

acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

SECTION 1: Identification

1.1 Product identifier

Trade name Eagle One Chrome Wheel Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Consumer uses

Uses advised against Do not use for squirting or spraying. Do not use

for products which come into direct contact with

the skin.

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc. 25225 Detroit Rd. Westlake OH 44145 United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)

e-mail: energizer@custhelp.com Website: http://data.energizer.com

1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727

This number is only available during the following

office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	1B	Skin Corr. 1B	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.6	A.6 carcinogenicity		Carc. 1A	H350
B.16	substance or mixture corrosive to metals	1	Met. Corr. 1	H290

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

United States: en Page: 1 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05, GHS08



- Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H350 May cause cancer.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P234 Keep only in original container.
P260 Do not breathe dusts or mists.
P280 Wear eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.
P390 Absorb spillage to prevent material damage.

P405 Store locked up.

P406 Store in corrosive resistant container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/international regula-

tions.

- Hazardous ingredients for labelling

sulphuric acid ... %, sodium octane-1-sulphonate monohydrate, ammonium bifluoride

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

United States: en Page: 2 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
phosphoric acid %	CAS No 7664-38-2	5 – < 10	Skin Corr. 1B / H314 Eye Dam. 1 / H318 Met. Corr. 1 / H290	
sodium octane-1-sulphon- ate monohydrate	CAS No 5324-84-5	1-<5	Skin Irrit. 2 / H315 Eye Dam. 1 / H318	
oxalic acid	CAS No 144-62-7	1-<5	Acute Tox. 4 / H302 Acute Tox. 4 / H312	<u>(1)</u>
ammonium bifluoride	CAS No 1341-49-7	1-<5	Acute Tox. 3 / H301 Skin Corr. 1B / H314 Eye Dam. 1 / H318	
Alcohol Ethoxylate	CAS No 68439-46-3	1-<5	Acute Tox. 4 / H302 Eye Dam. 1 / H318	
sulphuric acid %	CAS No 7664-93-9	<1	Skin Corr. 1A / H314 Eye Dam. 1 / H318 Carc. 1A / H350	

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first- aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

United States: en Page: 3 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2), Phosphorus oxides (PxOy)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

United States: en Page: 4 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Corrosive conditions

Store in corrosive resistant container with a resistant inner liner.

Control of the effects

Protect against external exposure, such as

Frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

United States: en Page: 5 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identifi- er	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Source
US	oxalic acid	144-62-7	PEL (CA)		1		2	Cal/OSHA PEL
US	oxalic acid	144-62-7	REL		1 (10 h)		2	NIOSH REL
US	oxalic acid	144-62-7	PEL		1			29 CFR 1910.1000
US	Oxalic acid, anhydrous	144-62-7	TLV®		1		2	ACGIH® 2018
US	phosphoric acid	7664-38-2	PEL (CA)		1		3	Cal/OSHA PEL
US	phosphoric acid	7664-38-2	REL		1 (10 h)		3	NIOSH REL
US	phosphoric acid	7664-38-2	TLV®		1		3	ACGIH® 2018
US	phosphoric acid	7664-38-2	PEL		1			29 CFR 1910.1000
US	sulfuric acid	7664-93-9	PEL (CA)		0.1		3	Cal/OSHA PEL
US	sulfuric acid	7664-93-9	REL		1 (10 h)			NIOSH REL
US	sulfuric acid	7664-93-9	PEL		1			29 CFR 1910.1000
US	sulfuric acid	7664-93-9	TLV®		0.2			ACGIH® 2018

Notation

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

United States: en Page: 6 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid	
Color	different	
Odor	characteristic	

Other safety parameters

pH (value)	2.8
Melting point/freezing point	not determined
Initial boiling point and boiling range	90.6 °C at 1,013 hPa
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	not determined
Vapor pressure	not determined
Density	1.068 ^g / _{cm³} at 20 °C
Vapor density	this information is not available
Relative density	1.088 at 20 °C (air = 1)
Solubility(ies)	not determined

United States: en Page: 7 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Solvent content	99.5 %
Solid content	0.5 %

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

United States: en Page: 8 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
oxalic acid	144-62-7	oral	500 ^{mg} / _{kg}
oxalic acid	144-62-7	dermal	1,100 ^{mg} / _{kg}
ammonium bifluoride	1341-49-7	oral	100 ^{mg} / _{kg}
Alcohol Ethoxylate	68439-46-3	oral	500 ^{mg} / _{kg}

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
sulphuric acid %	7664-93-9	1	Volume 54, 100F

Legend

Carcinogenic to humans

United States: en Page: 9 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
sulphuric acid %	7664-93-9	Known to be a hu- man carcinogen	9th Report on Carcinogens

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

United States: en Page: 10 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number 1760

14.2 UN proper shipping name Corrosive liquid, n.o.s.

Technical name (hazardous ingredients) phosphoric acid ... %, ammonium bifluoride

14.3 Transport hazard class(es)

Class 8 (corrosive substances)

14.4 Packing group II (substance presenting medium danger)

14.5 Environmental hazards non-environmentally hazardous acc. to the danger-

ous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number 1760

Proper shipping name Corrosive liquid, n.o.s.

- Particulars in the shipper's declaration UN1760, Corrosive liquid, n.o.s., (contains: phos-

phoric acid ... %, ammonium bifluoride), 8, II

- Reportable quantity (RQ) 10,000 lbs (4,540 kg) (ammonium bifluoride, sulphur-

ic acid ... %)

Class 8

Packing group II

United States: en Page: 11 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

Danger label(s)

8



Special provisions (SP) B2, IB2, T11, TP2, TP27

ERG No 154

International Maritime Dangerous Goods Code (IMDG)

UN number 1760

Proper shipping name CORROSIVE LIQUID, N.O.S.

Class 8
Marine pollutant Packing group II
Danger label(s) 8



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-A, S-B

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1760

Proper shipping name Corrosive liquid, n.o.s.

Class 8
Packing group II
Danger label(s) 8



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3

E2

Limited quantities (LQ)

0,5 L

United States: en Page: 12 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities

Name acc. to inventory	CAS No	Notes	Reportable quant- ity (pounds)	Threshold plan- ning quantity (pounds)
sulfuric acid	7664-93-9		1,000	1000

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name acc. to inventory	CAS No	Remarks	Effective date
sulfuric acid	7664-93-9	acid aerosols includ- ing mists, vapors, gas, fog, and other airborne forms of any particle size	1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sulphuric acid %	7664-93-9		1	1000 (454)
ammonium bifluoride	1341-49-7		1	100 (45,4)
phosphoric acid %	7664-38-2		1	5000 (2270)

Legend

Clean Air Act

none of the ingredients are listed

United States: en Page: 13 / 17

[&]quot;1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

New Jersey Worker and Community Right to Know Act

Right to Know Hazardous Substance List

			i e e e e e e e e e e e e e e e e e e e
Name acc. to inventory	CAS No	Remarks	Classifications
SULFURIC ACID (DIHYDROGEN SULFATE)	7664-93-9		CA CO R2
ammonium bifluoride	1341-49-7		СО
phosphoric acid	7664-38-2		СО
oxalic acid	144-62-7		СО

Legend

CA _____ Carcinogenic

CO R2

Corrosive Reactive - Second Degree

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and **Toxic Enforcement Act of 1987**

none of the ingredients are listed

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the tox- icity
Strong inorganic acid mists containing sulfuric acid			cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

United States: en Page: 14 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS Australian Inventory of Chemical Substances CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

ECSI

EC Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS) IECSC

INSQ ISHA-ENCS

KECI Korea Existing Chemicals Inventory New Zealand Inventory of Chemicals NZIoC

PICCS Philippine Inventory of Chemicals and Chemical Substances

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

United States: en Page: 15 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

	-
Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
ACGIH® 2018	From ACGIH®, 2018 TLVs® and BEIs® Book. Copyright 2018. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)

United States: en Page: 16 / 17



acc. to 29 CFR 1910.1200 App D

Eagle One Chrome Wheel Cleaner

Version number: GHS 1.1 Date of compilation: 2019-01-28

Abbr.	Descriptions of used abbreviations
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H350	May cause cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 17 / 17