

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 1 of 11

## Steel Reinforced Epoxy Resin - Twin Tube - Part A

### SECTION 1: Identification

#### Product identifier

**Product name:** Steel Reinforced Epoxy Resin - Twin Tube - Part A  
**Product code:** 8265, 8265S, 8265H, 8280, 8281, 8272, 8276, 8270, 8271, 8276H



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Not determined or not applicable.  
**Uses advised against:** Not determined or not applicable.  
**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

**Manufacturer:**  
**United States**  
J-B Weld Company, LLC  
400 CMH Road  
Sulphur Springs, TX 75482  
903-885-7696  
info@jbweld.com

#### Emergency telephone number:

**United States**  
CHEMTREC  
Transportation Emergencies (24 hour): 800-424-9300 or  
703-527-3887  
Poison Control Centers (24 hour): medical emergencies 800-222-1222

### SECTION 2: Hazard(s) identification

#### GHS classification:

Eye irritation, category 2A  
Skin irritation, category 2  
Skin sensitization, category 1

#### Label elements

##### Hazard pictograms:



**Signal word:** Warning

#### Hazard statements:

H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

#### Precautionary statements:

P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 2 of 11

## Steel Reinforced Epoxy Resin - Twin Tube - Part A

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P501 Dispose of contents and container in accordance with local regulations.

Hazards not otherwise classified: None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 1317-65-3	Calcium Carbonate	<50
CAS number: 25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	<30
CAS number: 14807-96-6	Talc Powder	<10
CAS number: 9003-36-5	Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	<5
CAS number: 2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	<5
CAS number: 65997-17-3	Glass, oxide, chemicals	<5

### Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

Fiberglass powder (CAS # 65997-17-3) is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Not determined or not applicable.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

#### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 3 of 11

### Steel Reinforced Epoxy Resin - Twin Tube - Part A

Gently blot or brush away excess product  
Wash with plenty of lukewarm, gently flowing water  
Get medical advice if skin irritation occurs or you feel unwell

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes  
If symptoms develop or persist, seek medical attention  
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open  
Remove contact lenses, if present and easy to do so  
Continue rinsing for 15-20 minutes  
Get medical advice if eye irritation persists

#### After swallowing:

Rinse mouth thoroughly  
Seek medical attention if irritation, discomfort, or vomiting persists

#### Most important symptoms and effects, both acute and delayed

##### Acute symptoms and effects:

Not determined or not applicable.

##### Delayed symptoms and effects:

Not determined or not applicable.

#### Immediate medical attention and special treatment

##### Specific treatment:

Not determined or not applicable.

##### Notes for the doctor:

Not determined or not applicable.

### SECTION 5: Firefighting measures

#### Extinguishing media

##### Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

##### Unsuitable extinguishing media:

Not determined or not applicable.

#### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

#### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

#### Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion  
Heating causes a rise in pressure, risk of bursting and combustion

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation  
Ensure air handling systems are operational  
Wear protective eye wear, gloves and clothing

#### Environmental precautions:

Should not be released into the environment  
Prevent from reaching drains, sewer or waterway

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 4 of 11

### Steel Reinforced Epoxy Resin - Twin Tube - Part A

#### Methods and material for containment and cleaning up:

- Wear protective eye wear, gloves and clothing
- Sweep or scoop up solid material while minimizing dust generation
- Dispose of contents / container in accordance with local regulations

#### Reference to other sections:

Not determined or not applicable.

### SECTION 7: Handling and storage

#### Precautions for safe handling:

- Use only with adequate ventilation.
- Avoid breathing dust.
- Do not eat, drink, smoke or use personal products when handling chemical substances.

#### Conditions for safe storage, including any incompatibilities:

- Keep container tightly sealed.
- Keep container dry.
- Store in a cool, well-ventilated area.

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States (OSHA)	Talc Powder	14807-96-6	OSHA PEL Ceiling 20 mppcf
	Calcium Carbonate	1317-65-3	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
	Calcium Carbonate	1317-65-3	OSHA PEL TWA 5 mg/m <sup>3</sup> (Respirable fraction)
ACGIH	Talc Powder	14807-96-6	ACGIH TLV TWA 2 mg/m <sup>3</sup> ; (Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Calcium Carbonate	1317-65-3	ACGIH TLV TWA 10.0 mg/m <sup>3</sup> ((Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Glass, oxide, chemicals	65997-17-3	8-Hour Exposure Limit (TLV-TWA): 1 fibers/cm <sup>3</sup>
NIOSH	Talc Powder	14807-96-6	NIOSH REL TWA 2.0 mg/m <sup>3</sup>
	Calcium Carbonate	1317-65-3	REL: 10 mg/m <sup>3</sup> (Total dust); 5 mg/m <sup>3</sup> (Respirable dust)
	Glass, oxide, chemicals	65997-17-3	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek] is: 3 fibers/cm <sup>3</sup>

#### Biological limit values:

No biological exposure limits noted for the ingredient(s).

#### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 5 of 11

## Steel Reinforced Epoxy Resin - Twin Tube - Part A

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Off White - Paste
Odor	Ethereal (slight)
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Closed cup: >93.3 °C (>199.9 °F) [Setaflash.] [Product does not sustain combustion.]
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	1.927
Solubilities	Insoluble in the following materials: cold water and hot water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	>220 °C (>428 °F)
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 6 of 11

## Steel Reinforced Epoxy Resin - Twin Tube - Part A

### Other information

Flammability	Non-flammable in the presence of the following materials or conditions: heat, shocks and mechanical impacts, oxidizing materials, reducing materials, combustible materials, organic materials, metals, acids, alkalis and moisture.
VOC Content	<1%

## SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

None known.

### Incompatible materials:

None known.

### Hazardous decomposition products:

None known.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
1,4-bis(2,3 epoxypropoxy)butane	dermal	LD50 - Rabbit - 1,130 mg/kg

### Skin corrosion/irritation

#### Assessment:

Causes skin irritation

#### Product data:

No data available.

#### Substance data:

Name	Result
Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	Causes skin irritation.
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Causes skin irritation.
1,4-bis(2,3 epoxypropoxy)butane	Causes skin irritation.

### Serious eye damage/irritation

#### Assessment:

Causes serious eye irritation

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 7 of 11

### Steel Reinforced Epoxy Resin - Twin Tube - Part A

#### Product data:

No data available.

#### Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Causes serious eye irritation.
1,4-bis(2,3 epoxypropoxy)butane	Causes serious eye irritation.

#### Respiratory or skin sensitization

##### Assessment:

May cause an allergic skin reaction

##### Product data:

No data available.

##### Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	May cause an allergic skin reaction.
Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	May cause an allergic skin reaction.
1,4-bis(2,3 epoxypropoxy)butane	May cause an allergic skin reaction.

#### Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

##### Substance data:

Name	Species	Result
Glass, oxide, chemicals	Not applicable	May cause cancer via inhalation.

#### International Agency for Research on Cancer (IARC):

Name	Classification
Glass, oxide, chemicals	Group 2B
Talc Powder	Group 3 - Not classifiable as to its carcinogenicity to humans

#### National Toxicology Program (NTP):

Name	Classification
Glass, oxide, chemicals	Reasonably anticipated to be human carcinogens

#### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

#### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 8 of 11

### Steel Reinforced Epoxy Resin - Twin Tube - Part A

No data available.

**Substance data:** No data available.

#### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

#### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

#### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

#### Information on likely routes of exposure:

No data available.

#### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

#### Other information:

No data available.

### SECTION 12: Ecological information

#### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	EC50 - Scenedesmus capricornutum - 9 mg/L - 48 h

#### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	NOEC Daphnia magna: 0.3 mg/L (21 d)

#### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

#### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

#### Mobility in soil



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 9 of 11

## Steel Reinforced Epoxy Resin - Twin Tube - Part A

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

## SECTION 15: Regulatory information

### United States regulations

Inventory listing (TSCA):

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 10 of 11

### Steel Reinforced Epoxy Resin - Twin Tube - Part A

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Listed
9003-36-5	Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	Listed
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	Listed
65997-17-3	Glass, oxide, chemicals	Listed
14807-96-6	Talc Powder	Listed
1317-65-3	Calcium Carbonate	Listed

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

**SARA Section 302 extremely hazardous substances:** Not determined.

**SARA Section 313 toxic chemicals:**

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
9003-36-5	Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	Not Listed
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	Not Listed
65997-17-3	Glass, oxide, chemicals	Not Listed
14807-96-6	Talc Powder	Not Listed
1317-65-3	Calcium Carbonate	Not Listed

**CERCLA:** Not determined.

**RCRA:** Not determined.

**Section 112(r) of the Clean Air Act (CAA):** Not determined.

**Massachusetts Right to Know:**

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
9003-36-5	Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	Not Listed
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	Not Listed
65997-17-3	Glass, oxide, chemicals	Listed
14807-96-6	Talc Powder	Listed
1317-65-3	Calcium Carbonate	Listed

**New Jersey Right to Know:**

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
9003-36-5	Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	Not Listed
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	Not Listed
65997-17-3	Glass, oxide, chemicals	Listed
14807-96-6	Talc Powder	Listed
1317-65-3	Calcium Carbonate	Listed

**New York Right to Know:**

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 11 of 11

### Steel Reinforced Epoxy Resin - Twin Tube - Part A

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
9003-36-5	Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	Not Listed
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	Not Listed
65997-17-3	Glass, oxide, chemicals	Not Listed
14807-96-6	Talc Powder	Not Listed
1317-65-3	Calcium Carbonate	Not Listed

#### Pennsylvania Right to Know:

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Not Listed
9003-36-5	Formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol	Not Listed
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane	Not Listed
65997-17-3	Glass, oxide, chemicals	Listed
14807-96-6	Talc Powder	Listed
1317-65-3	Calcium Carbonate	Listed

California Proposition 65: None of the ingredients are listed.

### SECTION 16: Other information

Abbreviations and Acronyms: None

#### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-0-0

HMIS: 3-0-0

Initial preparation date: 06.07.2023

End of Safety Data Sheet

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 1 of 11

## Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

### SECTION 1: Identification

#### Product identifier

**Product name:** Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube  
- Part B

**Product code:** 8276, 8270, 8271, 8276H



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Not determined or not applicable.

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

J-B Weld Company, LLC  
400 CMH Road  
Sulphur Springs, TX 75482  
903-885-7696  
info@jbweld.com

#### Emergency telephone number:

##### United States

CHEMTREC

Transportation Emergencies (24 hour): 800-424-9300 or  
703-527-3887

Poison Control Centers (24 hour): medical emergencies 800-222-1222

### SECTION 2: Hazard(s) identification

#### GHS classification:

Skin sensitization, category 1

#### Label elements

##### Hazard pictograms:



**Signal word:** Warning

#### Hazard statements:

H317 May cause an allergic skin reaction.

#### Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see supplemental first aid instructions on this label).

P363 Wash contaminated clothing before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P501 Dispose of contents and container in accordance with local regulations.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 2 of 11

## Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

Hazards not otherwise classified: None

### SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 72244-98-5	Curing Agent	<40
CAS number: 7727-43-7	Barium Sulphate	<30
CAS number: 1317-65-3	Calcium Carbonate	<30
CAS number: 14807-96-6	Talc Powder	<10
CAS number: 90-72-2	Amine Mix	<5
CAS number: 65997-17-3	Fiberglass Powder	<5
CAS number: 13463-67-7	Titanium Dioxide	<1

#### Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

Fiberglass powder (CAS # 65997-17-3) is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

### SECTION 4: First aid measures

#### Description of first aid measures

##### General notes:

Not determined or not applicable.

##### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

##### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

##### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

##### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

#### Most important symptoms and effects, both acute and delayed

##### Acute symptoms and effects:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 3 of 11

## Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

Not determined or not applicable.

### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

#### Unsuitable extinguishing media:

Not determined or not applicable.

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### Special precautions:

Not determined or not applicable.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

### Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

### Reference to other sections:

Not determined or not applicable.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 4 of 11

## Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

Store in a cool, well-ventilated area.

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States (OSHA)	Talc Powder	14807-96-6	OSHA PEL Ceiling 20 mppcf
	Calcium Carbonate	1317-65-3	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
	Titanium Dioxide	13463-67-7	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
	Calcium Carbonate	1317-65-3	OSHA PEL TWA 5 mg/m <sup>3</sup> (Respirable fraction)
	Barium Sulphate	7727-43-7	OSHA PEL TWA 15 mg/m <sup>3</sup> (Total dust)
	Barium Sulphate	7727-43-7	OSHA PEL TWA 5 mg/m <sup>3</sup> (Respirable fraction)
ACGIH	Barium Sulphate	7727-43-7	ACGIH TLV TWA 5.0 mg/m <sup>3</sup> (inhalable fraction, particulate containing no asbestos and < 1% crystalline silica)
	Talc Powder	14807-96-6	ACGIH TLV TWA 2 mg/m <sup>3</sup> ; (Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Titanium Dioxide	13463-67-7	ACGIH TLV TWA 10 mg/m <sup>3</sup>
	Calcium Carbonate	1317-65-3	ACGIH TLV TWA 10.0 mg/m <sup>3</sup> ((Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Fiberglass Powder	65997-17-3	8-Hour Exposure Limit (TLV-TWA): 1 fibers/cm <sup>3</sup>
NIOSH	Barium Sulphate	7727-43-7	NIOSH TWA 5.0 mg/m <sup>3</sup> (Respirable fraction)
	Talc Powder	14807-96-6	NIOSH REL TWA 2.0 mg/m <sup>3</sup>
	Barium Sulphate	7727-43-7	NIOSH TWA 10.0 mg/m <sup>3</sup> (Total dust)
	Calcium Carbonate	1317-65-3	REL: 10 mg/m <sup>3</sup> (Total dust); 5 mg/m <sup>3</sup> (Respirable dust)
	Titanium Dioxide	13463-67-7	IDLH: 5,000 mg/m <sup>3</sup>
	Fiberglass Powder	65997-17-3	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek] is: 3 fibers/cm <sup>3</sup>

#### Biological limit values:

No biological exposure limits noted for the ingredient(s).

#### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 5 of 11

## Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

### Appropriate engineering controls:

- Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.
- Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

### Personal protection equipment

#### Eye and face protection:

- Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

- Select glove material impermeable and resistant to the substance.
- Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

- If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

- Avoid contact with skin, eyes and clothing.
- Wash hands before breaks and at the end of work.
- Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Dark grey - Paste
Odor	Pungent. [Strong]
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Closed cup: >93.3°C (>199.9°F) [Setaflash.] [Product does not sustain combustion.]
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	1.902
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	>220 °C (>392 °F)
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 6 of 11

## Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

### Other information

VOC Content	<1%
-------------	-----

## SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

None known.

### Incompatible materials:

None known.

### Hazardous decomposition products:

None known.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Amine Mix	oral	LD50 - Rat - 1,200 mg/kg

### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Amine Mix	Causes skin irritation.

### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Amine Mix	Causes serious eye irritation.

### Respiratory or skin sensitization

#### Assessment:

May cause an allergic skin reaction

#### Product data:

No data available.

#### Substance data:

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 7 of 11

### Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

Name	Result
Curing Agent	May cause an allergic skin reaction.

#### Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Species	Result
Fiberglass Powder	Not applicable	May cause cancer via inhalation.
Titanium Dioxide	Not applicable.	Airborne, unbound particles of respirable size are known to cause cancer.

#### International Agency for Research on Cancer (IARC):

Name	Classification
Fiberglass Powder	Group 2B
Talc Powder	Group 3 - Not classifiable as to its carcinogenicity to humans
Titanium Dioxide	Group 2B

#### National Toxicology Program (NTP):

Name	Classification
Fiberglass Powder	Reasonably anticipated to be human carcinogens

#### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

#### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

#### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

#### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

#### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

#### Information on likely routes of exposure:

No data available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 8 of 11

## Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

### Substance data:

Name	Result
Curing Agent	NOEC - Daphnia magna (Water flea) - 3.5 mg/L - 21 d

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 9 of 11

## Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

Environmental hazards	None
Special precautions for user	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

## SECTION 15: Regulatory information

### United States regulations

#### Inventory listing (TSCA):

72244-98-5	Curing Agent	Listed
90-72-2	Amine Mix	Listed
65997-17-3	Fiberglass Powder	Listed
14807-96-6	Talc Powder	Listed
1317-65-3	Calcium Carbonate	Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Listed

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

**SARA Section 302 extremely hazardous substances:** Not determined.

#### SARA Section 313 toxic chemicals:

72244-98-5	Curing Agent	Not Listed
90-72-2	Amine Mix	Not Listed
65997-17-3	Fiberglass Powder	Not Listed
14807-96-6	Talc Powder	Not Listed
1317-65-3	Calcium Carbonate	Not Listed
13463-67-7	Titanium Dioxide	Not Listed
7727-43-7	Barium Sulphate	Listed

**CERCLA:** Not determined.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 10 of 11

### Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

RCRA: Not determined.

Section 112(r) of the Clean Air Act (CAA): Not determined.

#### Massachusetts Right to Know:

72244-98-5	Curing Agent	Not Listed
90-72-2	Amine Mix	Not Listed
65997-17-3	Fiberglass Powder	Listed
14807-96-6	Talc Powder	Listed
1317-65-3	Calcium Carbonate	Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Listed

#### New Jersey Right to Know:

72244-98-5	Curing Agent	Not Listed
90-72-2	Amine Mix	Not Listed
65997-17-3	Fiberglass Powder	Listed
14807-96-6	Talc Powder	Listed
1317-65-3	Calcium Carbonate	Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Listed

#### New York Right to Know:

72244-98-5	Curing Agent	Not Listed
90-72-2	Amine Mix	Not Listed
65997-17-3	Fiberglass Powder	Not Listed
14807-96-6	Talc Powder	Not Listed
1317-65-3	Calcium Carbonate	Not Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Not Listed

#### Pennsylvania Right to Know:

72244-98-5	Curing Agent	Not Listed
90-72-2	Amine Mix	Not Listed
65997-17-3	Fiberglass Powder	Listed
14807-96-6	Talc Powder	Listed
1317-65-3	Calcium Carbonate	Listed
13463-67-7	Titanium Dioxide	Listed
7727-43-7	Barium Sulphate	Listed

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.07.2023

Page 11 of 11

### Steel Reinforced Epoxy Hardener - Fast Cure - Twin Tube - Part B

California Proposition 65: ⚠️WARNING: Cancer – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

#### SECTION 16: Other information

**Abbreviations and Acronyms:** None

**Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 3-0-0

**HMIS:** 3-0-0

Initial preparation date: 06.07.2023

**End of Safety Data Sheet**