

Issuing Date 03-Apr-2007

Revision Date 07-Mar-2015

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Mothers Mag & Aluminum Polish

Other means of identification

Product Code(s) 05100, 05101, 05102, 05104, 35100, 55100

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Metal polish

Uses advised against No information available

Supplier's details

Supplier Address
MOTHERS POLISHES WAXES CLEANERS
5456 Industrial Drive
Huntington Beach, CA 92649
TEL: 714-891-3364
FAX: 714-893-1827

Emergency telephone number

Emergency Telephone Number Chemtrec Phone: 1-800-424-9300 (within the U.S.) or +1 703-527-3887 (outside the U.S.)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Aspiration Toxicity	Category 1
Flammable liquids	Category 4

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Danger
Hazard Statements
• May be fatal if swallowed and enters airways
•
• Combustible liquid.

**Appearance** White**Physical State** Solid.**Odor** Pine**Precautionary Statements****Prevention**

- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- None

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Fire

- In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep cool.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

36.04743% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Petroleum distillates, hydrotreated light	64742-47-8	25-50	*
Aluminum oxide	1344-28-1	25-50	*
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	<10	*
Triethanolamine	102-71-6	<10	*
Tall oil fatty acids	61790-12-3	<10	*
Hexylene glycol	107-41-5	<10	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures**Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Skin Contact

Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.

Inhalation

Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Ingestion Drink plenty of water. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician if necessary

Protection of First-aiders For personal protection see Section 8

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Aspiration into lungs can produce severe lung damage

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Foam. Dry powder. Dry chemical.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical

Combustible liquid. Vapors may travel to source of ignition and flash back. Thermal decomposition can lead to release of irritating gases and vapors.

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with the skin and the eyes. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Dam up. Soak up with inert absorbent material. Clean contaminated surface thoroughly. Keep in suitable and closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. Ensure adequate ventilation. Remove all sources of ignition.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m ³ STEL: 10 mg/m ³ (as oil mist)	TWA: 5 mg/m ³ (as oil mist)	-
Aluminum oxide 1344-28-1	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	-
Triethanolamine 102-71-6	TWA: 5 mg/m ³	-	-
Tall oil fatty acids 61790-12-3	5 mg/m ³ (resp) 10 mg/m ³ STEL (resp)	5 mg/m ³ (resp)	-
Hexylene glycol 107-41-5	Ceiling: 25 ppm	(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m ³	Ceiling: 25 ppm Ceiling: 125 mg/m ³

Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.
Skin and Body Protection Protective gloves.
Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Solid.	Appearance	White
Odor	Pine	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	55 °C	None known
Boiling Point/Boiling Range	No data available	None known
Flash Point	90 °C / 194 °F	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known

Vapor Density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Combustible material: may burn but does not ignite readily.

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%) <30

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None under normal use. Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	No known effect.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	Prolonged or repeated contact may dry skin and cause irritation. Causes mild skin irritation
Ingestion	Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
---------------	-----------	-------------	-----------------

Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Aluminum oxide	> 5000 mg/kg (Rat)	-	-
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Triethanolamine	= 4190 mg/kg (Rat)	> 2000 mg/kg (Rabbit) > 16 mL/kg (Rat)	-
Tall oil fatty acids	= 7600 mg/kg (Rat)	-	-
Hexylene glycol	= 3692 mg/kg (Rat)	12,3000 mg/kg (Rabbit)	> 310 mg/m ³ (Rat) 1 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available.
Mutagenic Effects No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Triethanolamine		Group 3		

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

Reproductive Toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Chronic Toxicity Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal
Target Organ Effects Respiratory system. Eyes. Skin. Central nervous system (CNS).
Aspiration Hazard May be fatal if swallowed and enters airways

Numerical measures of toxicity - Product

Acute Toxicity 36.04743% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 14428 mg/kg; Acute toxicity estimate
LD50 Dermal 25219 mg/kg; Acute toxicity estimate
Inhalation mg/L
dust/mist 57.1 mg/L; Acute toxicity estimate mg/L

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated light 64742-47-8		LC50 96 h: = 45 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.2 mg/L static (Lepomis macrochirus) LC50 96 h: = 2.4 mg/L static (Oncorhynchus mykiss)		LC50 96 h: = 4720 mg/L (Daphnia magna)
Aluminum oxide 1344-28-1		LC50 96 h: > 100 mg/L semistatic (Salmo trutta)		LC50 48 h: > 100 mg/L (daphnia magna)
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	EC50 96 h: = 450 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 800 mg/L static (Pimephales promelas)		EC50 48 h: > 100 mg/L (Daphnia magna)

Triethanolamine 102-71-6	EC50 72 h: = 216 mg/L (Desmodesmus subspicatus) EC50 96 h: = 169 mg/L (Desmodesmus subspicatus)	LC50 96 h: 10600 - 13000 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1000 mg/L static (Pimephales promelas) LC50 96 h: 450 - 1000 mg/L static (Lepomis macrochirus)	EC50 > 10000 mg/L 30 min	EC50 24 h: = 1386 mg/L (Daphnia magna)
Tall oil fatty acids 61790-12-3	EC50 72 h: >= 1000 mg/L (Pseudokirchneriella subcapitata)			
Hexylene glycol 107-41-5		LC50 96 h: 10500 - 11000 mg/L flow-through (Pimephales promelas) LC50 96 h: = 10000 mg/L static (Lepomis macrochirus) LC50 96 h: = 8690 mg/L flow-through (Pimephales promelas) LC50 96 h: = 10700 mg/L static (Pimephales promelas)	EC50 = 3038 mg/L 5 min	EC50 48 h: 2700 - 3700 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Triethanolamine	-2.53
Tall oil fatty acids	5.98
Hexylene glycol	0.13986

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

California Hazardous Waste Codes 331

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
EINECS Complies

ELINCS Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Aluminum oxide	X	X	X		X
Solvent naphtha (petroleum), medium aliphatic	X				
Triethanolamine	X	X	X		X
Hexylene glycol	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and Chemical Hazards N/A
HMIS	Health Hazard 2	Flammability 2	Physical Hazard 0	Personal Protection B

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 03-Apr-2007
Revision Date 07-Mar-2015
Revision Note Update to Format.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet