

SAFETY DATA SHEET

Revision Date 11-Dec-2018 Version 4

1. IDENTIFICATION

Product identifier

Product Name 98H HIGH TACK GASKET SEALANT 4 FL.OZ

Other means of identification

Product Code 80062

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Emergency Overview

Signal word Danger

Causes skin irritation
Causes serious eye irritation

May cause an allergic skin reaction

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor



Appearance Red Physical state Liquid Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Use non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity 35.4066 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
ACETONE	67-64-1	15 - 40
N-HEXANE	110-54-3	10 - 30
ROSIN	8050-09-7	7 - 13

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Call a physician or poison control center immediately. Do NOT induce

vomiting.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire

Specific hazards arising from the chemical

Highly flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation, especially in

confined areas. Wash thoroughly after handling. Use personal protective equipment as

required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal. Use

personal protective equipment as required.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Remove all sources of ignition. Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Store locked up.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	-
		(vacated) STEL: 2400 mg/m ³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
N-HEXANE	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 180 mg/m ³
		(vacated) TWA: 180 mg/m ³	
ROSIN	-	(vacated) TWA: 0.1 mg/m ³	TWA: 0.1 mg/m³ Formaldehyde
8050-09-7		Formaldehyde	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations

Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protectionUse NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Red
Odor Solvent

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information availableMelting point / freezing point No information available

Boiling point / boiling range $57 \, ^{\circ}\text{C} \, / \, 135 \, ^{\circ}\text{F}$ Flash point $-18 \, ^{\circ}\text{C} \, / \, 0 \, ^{\circ}\text{F}$

Evaporation rate > 1 Ether = 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 13.0%
Lower flammability limit: 2.0%
Vapor pressure 400 mm Hg

Vapor density 2.5 Air = 1

Relative density 0.872

Water solubility Partially soluble

Solubility(ies) No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available No information available **Oxidizing properties**

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 16.6%

DensityNo information availableBulk densityNo information availableSADT (self-accelerating)No information available

decomposition temperature)

10. STABILITY AND REACTIVITY

Reactivity

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure if inhaled. May

cause drowsiness or dizziness.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and

pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
67-64-1			
N-HEXANE	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
110-54-3			
ROSIN	= 7600 mg/kg (Rat) = 3000 mg/kg	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
8050-09-7	(Rat)		

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. **Germ cell mutagenicity** No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Target Organ Effects Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system,

Skin, Thyroid.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 9326 mg/kg
ATEmix (dermal) 6387 mg/kg
ATEmix (inhalation-dust/mist) 178.2 mg/l
ATEmix (inhalation-vapor) 186367 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

35.6183 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
ACETONE	-0.24
67-64-1	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE	Ignitable
67-64-1	
N-HEXANE	Toxic
110-54-3	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID No 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group II
Emergency Response Guide 128

Number

<u>IATA</u>

UN/ID No ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

IMDG

UN/ID No 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group

EmS-No F-E, S-D

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL/NDSL Complies
EINECS/ELINCS Not determined
ENCS Not determined
IECSC Complies
KECL Complies
PICCS Complies
AICS Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
N-HEXANE - 110-54-3	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes

Chronic Health HazardYesFire hazardYesSudden release of pressure hazardNoReactive HazardNo

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	=	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
N-HEXANE	5000 lb	-	RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
N-HEXANE - 110-54-3	Developmental	
RHODAMINE - 81-88-9	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
N-HEXANE	X	X	X
110-54-3			
ROSIN	-	-	X
8050-09-7			
RHODAMINE	X	X	X
81-88-9			

Revision Date 11-Dec-2018

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 -

HMIS Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 11-Dec-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet