



Safety Data Sheet

Copyright, 2020, Meguiar's Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 26-6638-6
Issue Date: 05/26/20

Version Number: 6.02
Supersedes Date: 04/25/19

SECTION 1: Identification

1.1. Product identifier

Mirror Glaze® Hi-Tech Yellow Wax, M26 [M2601, M2616]

Product Identification Numbers

14-1000-1205-4, 14-1000-1208-8, 14-1000-1209-6
7100154157, 7100151945, 7100216339

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Premium, high-gloss wax

1.3. Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	17991 Mitchell South, Irvine, CA 92614, USA
Telephone:	949-752-8000 (Fax: 949-752-5784)

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Carcinogenicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Health Hazard |

Pictograms**Hazard Statements**

Suspected of causing cancer.

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.

Response:

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

1% of the mixture consists of ingredients of unknown acute dermal toxicity.

1% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Non-Hazardous Ingredients	Mixture	40 - 70 Trade Secret *
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	10 - 30 Trade Secret *
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	64742-48-9	3 - 7 Trade Secret *
Clay	Trade Secret*	3 - 7 Trade Secret *
Carnauba Wax	8015-86-9	1 - 5 Trade Secret *
Poly(Dimethylsiloxane)	63148-62-9	1 - 5 Trade Secret *
White Mineral Oil (Petroleum)	8042-47-5	0.1 - 1 Trade Secret *
Synthetic Hydrocarbon Mixture	Trade Secret*	0.1 - 1 Trade Secret *
Titanium Dioxide	13463-67-7	< 0.3 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Formaldehyde
Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance****Physical state**

Liquid

Color

Light Yellow

Odor

Banana

Odor threshold

No Data Available

pH

7.5 - 8.5

Melting point

Not Applicable

Boiling Point

390 °F

Flash Point> 200 °F [Test Method: Pensky-Martens Closed Cup]
[Details: D93-90]**Evaporation rate**

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density0.95 g/cm³**Specific Gravity**

0.95 [Ref Std: WATER=1]

Solubility in Water

Moderate

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

Not Applicable

Decomposition temperature

No Data Available

Viscosity

25,000 - 37,000 centipoise

Molecular weight

No Data Available

Volatile Organic Compounds

14.97 % weight

VOC Less H₂O & Exempt Solvents

543.59 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May cause additional health effects (see below).

Skin Contact:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
------------	---------	-------------------	------------

Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
------------------	------------	-------------------------------	---------------------------------------------

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
Clay	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Clay	Ingestion	Rat	LD50 > 2,000 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Carnauba Wax	Dermal		LD50 estimated to be > 5,000 mg/kg
Carnauba Wax	Ingestion	Rat	LD50 > 8,800 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Minimal irritation
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Rabbit	Minimal irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Carnauba Wax	Professional judgement	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Rabbit	Mild irritant
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Carnauba Wax	Professional judgement	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea pig	Not classified
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Guinea pig	Not classified
White Mineral Oil (Petroleum)	Guinea pig	Not classified
Titanium Dioxide	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In vivo	Not mutagenic
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In Vitro	Not mutagenic
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In vivo	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not available	Not carcinogenic
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not available	Not carcinogenic
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for development	Rat	NOAEL Not available	1 generation
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for female reproduction	Not available	NOAEL NA	1 generation
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for male reproduction	Not available	NOAEL NA	28 days
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for development	Not applicable	NOAEL NA	during gestation
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350	13 weeks

				mg/kg/day	
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

General Transportation Statement: This product does not require classification by DOT, IATA, ICAO or IMDG.

Please contact the emergency numbers listed on the first page of the SDS for Transportation Information for this material.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Hazard Not Otherwise Classified (HNOC)

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 26-6638-6
Issue Date: 05/26/20

Version Number: 6.02
Supersedes Date: 04/25/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com