# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 12/09/2021 Revision date: 12/20/2021 Supersedes: 08/31/2020 Version: 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

Product form : Mixture

Product name Shop Pro Carb Cleaner Non-VOC

Product code SP-CARB

#### Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carburetor Cleaner

#### 1.3. Details of the supplier of the safety data sheet

Autozone

PO Box 2198

Memphis, TN 38101

T 901-495-7522

#### **Emergency telephone number**

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### **SECTION 2: Hazards identification**

### Classification of the substance or mixture

#### **GHS US classification**

Flammable aerosol Category 2

Gases under pressure Compressed gas

Acute toxicity (oral) Category 3

Acute toxicity (dermal) Category 3
Acute toxicity (inhalation:dust,mist) Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2

Carcinogenicity Category 2

Reproductive toxicity Category 2

Specific target organ toxicity (single exposure) Category 1

Specific target organ toxicity — Single exposure, Category 3,

Narcosis

Specific target organ toxicity (repeated exposure) Category 2

H223 Flammable aerosol

H280 Contains gas under pressure; may explode if heated

H301 Toxic if swallowed

H311 Toxic in contact with skin

H332 Harmful if inhaled H315 Causes skin irritation

H319 Causes serious eye irritation

H351 Suspected of causing cancer

H361 Suspected of damaging fertility or the unborn child

H370 Causes damage to organs

H336 May cause drowsiness or dizziness

H373 May cause damage to organs through prolonged or repeated exposure

Full text of H- and EUH-statements: see section 16

#### **Label elements**

# **GHS US labeling**

Hazard pictograms (GHS US)











Signal word (GHS US) : Danger

Hazard statements (GHS US) H223 - Flammable aerosol

H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

H361 - Suspected of damaging fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other ignition source. P251 - Pressurized container: Do not pierce or burn, even after use.

P260 - Do not breathe dust, fumes, gas, mist, vapor spray

P261 - Avoid breathing dust,fume,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling

P270 - Do not eat, drink or smoke when using this product.

EN (English US) 20/12/2021 1/12

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P307+P311 - If exposed: Call a poison center/doctor.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment: See section 4.1 on SDS

P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards which do not result in classification

: Contains gas under pressure; may explode if heated. None under normal conditions.

#### **Unknown acute toxicity (GHS US)**

No data available

### **SECTION 3: Composition/Information on ingredients**

#### **Substances**

Not applicable

#### **Mixtures**

Name	Product identifier	%	GHS US classification
Toluene	(CAS-No.) 108-88-3	30 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Acetone	(CAS-No.) 67-64-1	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methanol	(CAS-No.) 67-56-1	10 – 30	Flam. Liq. 2, H225 STOT SE 1, H370
Carbon Dioxide, Liquefied, Under Pressure	(CAS-No.) 124-38-9	5 – 10	Press. Gas (Comp.), H280

Comments : Hazard classification of this material is based on the worst possible case

# **SECTION 4: First aid measures**

First-aid measures after ingestion

# **Description of first aid measures**

First-aid measures general : Never give anything by mouth to an unconscious person. Suspected of causing cancer. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or

doctor/physician. Specific treatment: See section 4.1 on SDS.

First-aid measures after inhalation Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call

a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact Immediately call a poison center or doctor/physician. Remove/Take off immediately all

contaminated clothing. Wash with plenty of soap and water. Specific measures (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment: See section 4.1 on SDS.

Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with First-aid measures after eye contact water for several minutes. Obtain medical attention if pain, blinking or redness persists. Direct

> contact with the eyes is likely to be irritating. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a

poison center or doctor/physician. Specific treatment: See section 4.1 on SDS. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child. Causes damage to organs.

20/12/2021 EN (English US) 2/12

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation Shortness of breath. Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.

Symptoms/effects after skin contact Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin. Causes skin irritation.

Toxic if swallowed. Swallowing a small quantity of this material will result in serious health Symptoms/effects after ingestion hazard.

#### Indication of any immediate medical attention and special treatment needed

No additional information available

# **SECTION 5: Firefighting measures**

#### **Extinguishing media**

: Foam. Dry powder. Carbon dioxide. Water spray. Sand. Suitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

#### Special hazards arising from the substance or mixture

: Can become highly flammable in use. Flammable aerosol. Fire hazard

Explosion hazard Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

#### Advice for firefighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

Other information Aerosol Level 2

#### **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

General measures : No flames, no sparks. Eliminate all sources of ignition. Evacuate area. No open flames. No

smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

: Safety glasses. Gloves. Protective equipment

**Emergency procedures** Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Ventilate area. **Emergency procedures** 

### **Environmental precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### Methods and material for containment and cleaning up

For containment Contain released product, collect/pump into suitable containers. Dam up the liquid spill, Pluq

the leak, cut off the supply

Methods for cleaning up : Store away from other materials.

#### Reference to other sections

See Heading 8. Exposure controls and personal protection.

# **SECTION 7: Handling and storage**

#### Precautions for safe handling

Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or Additional hazards when processed

burn, even after use.

Precautions for safe handling Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Avoid breathing dust,fume,gas,mist,vapor spray. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Do not

breathe dust,fumes,gas,mist,vapor spray.

Always wash hands after handling the product. Wash contaminated clothing before reuse. Hygiene measures Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling.

20/12/2021 EN (English US) 3/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Proper grounding procedures to avoid static

electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to

temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

### 7.3. Specific end use(s)

Follow Label Directions.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Shop Pro Carb Cleaner Non-VOC		
No additional information available		
Methanol (67-56-1)	Methanol (67-56-1)	
USA - ACGIH - Occupational Exposure Limit	ts	
ACGIH OEL TWA	262 mg/m³	
ACGIH OEL TWA [ppm]	200 ppm	
ACGIH OEL STEL	328 mg/m³	
ACGIH OEL STEL [ppm]	250 ppm	
USA - OSHA - Occupational Exposure Limit	S	
OSHA PEL (TWA) [1]	260 mg/m³	
OSHA PEL (TWA) [2]	200 ppm	
USA - NIOSH - Occupational Exposure Limit	ts	
NIOSH REL (TWA)	260 mg/m³	
NIOSH REL TWA [ppm]	200 ppm	
NIOSH REL (Ceiling)	325 mg/m³	
NIOSH REL C [ppm]	250 ppm	
Carbon Dioxide, Liquefied, Under Pressure	(124-38-9)	
USA - ACGIH - Occupational Exposure Limit	ts	
ACGIH OEL TWA	9000 mg/m³	
ACGIH OEL TWA [ppm]	5000 ppm	
ACGIH OEL STEL	54000	
ACGIH OEL STEL [ppm]	30000 ppm	
USA - OSHA - Occupational Exposure Limit	s	
OSHA PEL (TWA) [1]	9000 mg/m³	
OSHA PEL (TWA) [2]	5000 ppm	
USA - NIOSH - Occupational Exposure Limit	ts	
NIOSH REL (TWA)	9000 mg/m <sup>3</sup>	
NIOSH REL TWA [ppm]	5000 ppm	
NIOSH REL (Ceiling)	54000 mg/m³	
NIOSH REL C [ppm]	30000 ppm	
Toluene (108-88-3)		
USA - ACGIH - Occupational Exposure Limit	ts	
ACGIH OEL TWA [ppm]	20 ppm	
Acetone (67-64-1)		
USA - ACGIH - Occupational Exposure Limit	ts	
ACGIH OEL TWA	1188 mg/m³	
ACGIH OEL TWA [ppm]	500 ppm	
ACGIH OEL STEL	1782 mg/m³	
ACGIH OEL STEL [ppm]	750 ppm	
USA - OSHA - Occupational Exposure Limit		
OSHA PEL (TWA) [1]	2400 mg/m³	
OSHA PEL (TWA) [2]	1000 ppm	
USA - NIOSH - Occupational Exposure Limit		
NIOSH REL (TWA)	590 mg/m³	

20/12/2021 EN (English US) 4/12

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NIOSH REL TWA [ppm] 250 ppm

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Local exhaust venilation, vent hoods.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

#### Materials for protective clothing:

GIVE EXCELLENT RESISTANCE:

#### Hand protection:

Wear protective gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### Personal protective equipment symbol(s):





#### Other information:

Do not eat, drink or smoke during use.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Aerosol Appearance : Liquid.

Color : Colourless to light yellow.
Odor : Strong . Solvent-like odour.

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available Freezing point : No data available

Boiling point : 111 °C (Lowest Component)

Flash point : 4 °C (Lowest Component)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : 0.83

Solubility : Insoluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Partition coefficient n-octanol/water (Log Kow) : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

20/12/2021 EN (English US) 5/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion limits : No data available

9.2. Other information

VOC content : 68.4 %

Gas group : Compressed gas

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

# 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

## 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Toxic if swallowed.

Acute toxicity (dermal) : Toxic in contact with skin.

Acute toxicity (inhalation) : Harmful if inhaled.

ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h

Methanol (67-56-1)	
LD50 oral rat	≥ 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 Inhalation - Rat	128.2 mg/l/4h Air
ATE US (dermal)	17100 mg/kg body weight
ATE US (vapors)	128.2 mg/l/4h
ATE US (dust, mist)	128.2 mg/l/4h

Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	> 5000 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	28.1 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	5580 mg/kg body weight

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 Inhalation - Rat [ppm]	30000 ppm/4h (Rat; Experimental value)
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
ATE US (gases)	30000 ppmV/4h
ATE US (vapors)	71 mg/l/4h
ATE US (dust, mist)	71 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

20/12/2021 EN (English US) 6/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Suspected of causing cancer.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Causes damage to organs. May cause drowsiness or dizziness.

Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Toluene (108-88-3)		
	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
	Asniration hazard	Not classified

Viscosity, kinematic : No data available

Potential Adverse human health effects and

Based on available data, the classification criteria are not met. Harmful if inhaled. Toxic if swallowed. Toxic in contact with skin.

symptoms Symptoms/effects

: Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation

Shortness of breath. Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.

Symptoms/effects after skin contact

Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin. Causes skin irritation.

Symptoms/effects after ingestion

Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

hazard.

# **SECTION 12: Ecological information**

# **Toxicity**

Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semistatic system, Fresh water, Experimental value, Locomotor effect)
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
LC50 - Fish [1]	35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal)
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value, Lethal)
Acetone (67-64-1)	
LC50 - Fish [1]	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)
EC50 - Crustacea [1]	8800 mg/l (48 h; Daphnia pulex)
EC50 - Crustacea [1] LC50 - Fish [2]	8800 mg/l (48 h; Daphnia pulex) 5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
• •	
LC50 - Fish [2]	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
LC50 - Fish [2] TLM - Fish [1]	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss) 13000 ppm (96 h; Gambusia affinis; Turbulent water)
LC50 - Fish [2] TLM - Fish [1] TLM - Fish [2]	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss) 13000 ppm (96 h; Gambusia affinis; Turbulent water) > 1000 ppm (96 h; Pisces)
LC50 - Fish [2] TLM - Fish [1] TLM - Fish [2] Threshold limit - Other aquatic organisms [1]	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss) 13000 ppm (96 h; Gambusia affinis; Turbulent water) > 1000 ppm (96 h; Pisces) 3000 mg/l (Plankton)

#### 12.2. Persistence and degradability

Shop Pro Carb Cleaner Non-VOC	
Persistence and degradability	Not established.
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Persistence and degradability	Biodegradability: not applicable. Not established.

20/12/2021 EN (English US) 7/12

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Dioxide, Liquened, Onder Fressure (1	24-30-3)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance
ThOD	3.13 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.69
Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
12.3. Bioaccumulative potential	
Shop Pro Carb Cleaner Non-VOC	
Bioaccumulative potential	Not established.
•	1 111 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Methanol (67-56-1) BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.
<u>'</u>	
Carbon Dioxide, Liquefied, Under Pressure (1	1
Partition coefficient n-octanol/water (Log Pow)	0.83 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Toluene (108-88-3)	
BCF - Fish [1]	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces)
BCF - Other aquatic organisms [1]	3
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative. Not established.
12.4. Mobility in soil	
Methanol (67-56-1)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
Carbon Dioxide, Liquefied, Under Pressure (1	24-38-9)
Ecology - soil	Not applicable (gas).
Toluene (108-88-3)	
Surface tension	27730 mN/m (25 °C, 0.05 %)
Ecology - soil	Low potential for adsorption in soil.
Acetone (67-64-1)	<u>.                                      </u>
Surface tension	0.0237 N/m (20 °C)
	3.0201 Fam (20 0)
12.5. Other adverse effects	
Effect on global warming	: No known effects from this product.
Other information	: Avoid release to the environment.

20/12/2021 EN (English US) 8/12

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

# **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

US DOT (ground) (DOT) : UN1950 Aerosols (Flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

Flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail : 75 kg
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Other information : No supplementary information available.

#### Transport by sea

UN-No. (IMDG) : 1950

Class (IMDG) : 2.1 - Flammable gases
Hazard labels (IMDG) : 2.1 - Flammable gases
6.1 - Toxic substances



#### Air transport

UN-No. (IATA) : 1950
Proper Shipping Name (IATA) : Aerosols

Class (IATA) : 2.1 - Gases : Flammable

### **SECTION 15: Regulatory information**

# 15.1. US Federal regulations

Shop Pro Carb Cleaner Non-VOC	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Sudden release of pressure hazard Delayed (chronic) health hazard
Methanol (67-56-1)	

 Methanol (67-56-1)

 Listed on the United States TSCA (Toxic Substances Control Act) inventory

 Subject to reporting requirements of United States SARA Section 313

 CERCLA RQ
 5000 lb

20/12/2021 EN (English US) 9/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard	
SARA Section 313 - Emission Reporting	1 %	
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard	
Acetone (67-64-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard	

# 15.2. International regulations

#### **CANADA**

Shop Pro Carb Cleaner Non-VOC			
WHMIS Classification	Class B Division 5 - Flammable Aerosol		
Methanol (67-56-1)			
Listed on the Canadian DSL (Domestic Substances List)			
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)			
Listed on the Canadian DSL (Domestic Substances List)			
Acetone (67-64-1)			
Listed on the Canadian DSL (Domestic Substances List)			
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects		

# **EU-Regulations**

#### Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

# Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

## Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

### Methanol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

# Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

### Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

#### 15.3. US State regulations

Shop Pro Carb Cleaner Non-VOC()	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No

20/12/2021 EN (English US) 10/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Shop Pro Carb Cleaner No	on-VOC()				
U.S California - Proposition 65 - Reproductive Toxicity - Female		No			
U.S California - Proposition 65 - Reproductive Toxicity - Male		No			
State or local regulations		U.S California - Proposition 65			
Methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	Yes	No	No		
Carbon Dioxide, Liquefied	l, Under Pressure (124-38-	9)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
Toluene (108-88-3)			•		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
Acetone (67-64-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
Yes	Yes	No	Yes		
Methanol (67-56-1)					

# State or local regulations

- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List U.S. New York City Right to Know Hazardous Substances List

# Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

#### State or local regulations

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New York City Right to Know Hazardous Substances List
- U.S. Pennsylvania RTK (Right to Know) List

### Acetone (67-64-1)

#### State or local regulations

U.S. - California - Proposition 65

Benzene 71-43-2

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

# **SECTION 16: Other information**

Other information : None.

Full text of H-phrases:

on in princede.	
H223	Flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation

20/12/2021 EN (English US) 11/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H319	Causes serious eye irritation
	,
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated
	exposure

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause

temporary incapacitation or residual injury.


NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended

solids) that can be ignited under almost all ambient

temperature conditions.

: 0 - Material that in themselves are normally stable, even

under fire conditions.



#### **Hazard Rating**

NFPA reactivity

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard

Personal protection : B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

20/12/2021 EN (English US) 12/12