

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 12/10/2021

Revision date: 11/05/2021

Supersedes: 11/21/2021

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Shop Pro Carb Cleaner 10% VOC
Product code : SP-CARB-CA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carburetor Cleaner

1.3. Details of the supplier of the safety data sheet

Autozone
PO Box 2198
Memphis, TN 38101
T 901-495-7522

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable aerosol Category 2	H223 Flammable aerosol
Gases under pressure Compressed gas	H280 Contains gas under pressure; may explode if heated
Serious eye damage/eye irritation Category 2A	H319 Causes serious eye irritation
Reproductive toxicity Category 2	H361 Suspected of damaging fertility or the unborn child
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336 May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	H373 May cause damage to organs through prolonged or repeated exposure

Full text of H- and EUH-statements: see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H223 - Flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.
P260 - Do not breathe dust, fumes, gas, mist, vapor spray
P261 - Avoid breathing dust, fume, gas, mist, vapor spray
P264 - Wash affected areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards which do not result in classification : Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acetone	(CAS-No.) 67-64-1	≥ 95	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Carbon Dioxide, Liquefied, Under Pressure	(CAS-No.) 124-38-9	5 – 10	Press. Gas (Comp.), H280
Toluene	(CAS-No.) 108-88-3	5 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be irritating. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation : Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol Level 2.

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.
Emergency procedures : Evacuate area. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, collect/pump into suitable containers. Dam up the liquid spill. Plug the leak, cut off the supply.
Methods for cleaning up : Carefully collect the spill/leftovers. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse. Wash affected areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Shop Pro Carb Cleaner 10% VOC	
No additional information available	
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	9000 mg/m ³
ACGIH OEL TWA [ppm]	5000 ppm
ACGIH OEL STEL	54000
ACGIH OEL STEL [ppm]	30000 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	9000 mg/m ³
OSHA PEL (TWA) [2]	5000 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	9000 mg/m ³

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NIOSH REL TWA [ppm]	5000 ppm
NIOSH REL (Ceiling)	54000 mg/m ³
NIOSH REL C [ppm]	30000 ppm
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1188 mg/m ³
ACGIH OEL TWA [ppm]	500 ppm
ACGIH OEL STEL	1782 mg/m ³
ACGIH OEL STEL [ppm]	750 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	2400 mg/m ³
OSHA PEL (TWA) [2]	1000 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	590 mg/m ³
NIOSH REL TWA [ppm]	250 ppm
Toluene (108-88-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Local exhaust ventilation, vent hoods.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

Materials for protective clothing:

GIVE EXCELLENT RESISTANCE:

Hand protection:

In case of repeated or prolonged contact wear gloves. Gloves. protective gloves. Wear protective gloves

Eye protection:

Safety glasses. Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Aerosol
Appearance : Liquid.
Color : Colourless to light yellow.
Odor : Strong odour. Solvent-like odour.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: No data available
Freezing point	: No data available
Boiling point	: 56 °C (Lowest Component)
Flash point	: -18 °C (Lowest Component)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.795
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

VOC content	: 8.3 %
Gas group	: Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 Inhalation - Rat [ppm]	30000 ppm/4h (Rat; Experimental value)
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
ATE US (gases)	30000 ppmV/4h
ATE US (vapors)	71 mg/l/4h
ATE US (dust, mist)	71 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	> 5000 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)	
LC50 Inhalation - Rat	28.1 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	5580 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.

Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Suspected of damaging fertility or the unborn child. Causes damage to organs.
Symptoms/effects after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
LC50 - Fish [1]	35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal)
Acetone (67-64-1)	
LC50 - Fish [1]	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)
EC50 - Crustacea [1]	8800 mg/l (48 h; Daphnia pulex)
LC50 - Fish [2]	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
TLM - Fish [1]	13000 ppm (96 h; Gambusia affinis; Turbulent water)
TLM - Fish [2]	> 1000 ppm (96 h; Pisces)
Threshold limit - Other aquatic organisms [1]	3000 mg/l (Plankton)
Threshold limit - Other aquatic organisms [2]	28 mg/l (Protozoa)
Threshold limit - Algae [1]	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit - Algae [2]	3400 mg/l (48 h; Chlorella sp.)
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value, Lethal)

12.2. Persistence and degradability

Shop Pro Carb Cleaner 10% VOC	
Persistence and degradability	Not established.
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Persistence and degradability	Biodegradability: not applicable. Not established.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test) data on mobility of the substance available. Not established.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)	
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69

12.3. Bioaccumulative potential

Shop Pro Carb Cleaner 10% VOC	
Bioaccumulative potential	Not established.
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0.83 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces)
BCF - Other aquatic organisms [1]	3
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative. Not established.
Toluene (108-88-3)	
BCF - Fish [1]	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Ecology - soil	Not applicable (gas).
Acetone (67-64-1)	
Surface tension	0.0237 N/m (20 °C)
Toluene (108-88-3)	
Surface tension	27730 mN/m (25 °C, 0.05 %)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Effect on global warming : No known effects from this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

US DOT (ground) (DOT) : UN1950 Aerosols (Flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials
Other information	: No supplementary information available.

Transport by sea

UN-No. (IMDG)	: 1950
Class (IMDG)	: 2.1 - Flammable gases

Air transport

UN-No. (IATA)	: 1950
Proper Shipping Name (IATA)	: Aerosols
Class (IATA)	: 2.1 - Gases : Flammable

SECTION 15: Regulatory information

15.1. US Federal regulations

Shop Pro Carb Cleaner 10% VOC	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard
Acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA

Shop Pro Carb Cleaner 10% VOC	
WHMIS Classification	Class B Division 5 - Flammable Aerosol
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Listed on the Canadian DSL (Domestic Substances List)	
Acetone (67-64-1)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Acetone (67-64-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) - Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

Shop Pro Carb Cleaner 10% VOC()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - California - Proposition 65

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Acetone (67-64-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	No	Yes	

Toluene (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

State or local regulations

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York City - Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

Acetone (67-64-1)

State or local regulations

U.S. - California - Proposition 65
Benzene 71-43-2
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H223	Flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness


Shop Pro Carb Cleaner 10% VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

- Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
- Flammability : 3 Serious Hazard
- Physical : 1 Slight Hazard
- Personal protection : B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.