

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: NO TOUCH SERIOUSLY WET EXTREME TIRE SHINE 15 OZ AE
Item No: NTSW15-6
Product Type: Aerosol protectant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
ACETONE 67-64-1	40-70	500 ppm TWA; 750 ppm STEL	1000 ppm TWA; 2400 mg/m ³ TWA
POLYDIMETHYLSILOXANE 63148-62-9	10-30	Not Listed	Not Listed
CARBON DIOXIDE 124-38-9	5-15	5000 ppm TWA	5000 ppm TWA
SYNTHETIC ISOPARAFFINIC HYDROCARBON 64741-66-8	5-15	Not established	400 ppm
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	5-15	Not Listed	100 ppm TWA
DIMETHYLCYCLOSILOXANE 69430-24-6	5-15	Not Listed	Not Listed
HEXAMETHYLCYCLOTRISILOXAN E 541-05-9	<5	Not Listed	Not Listed
OCTAMETHYLCYCLOTETRAILOX ANE 556-67-2	<5	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation
Primary Routes of Entry: Eye and skin contact, inhalation
Signs and Symptoms of Exposure: Eyes: Exposure to liquid or vapor causes mild eye irritation. Symptoms may include burning, tearing, redness, stinging, blurred vision and corneal injury. Inhaling may cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression. Skin redness.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
ACETONE 67-64-1	40-70	Not known	A4 - Not Classifiable as a Human Carcinogen	Not known

Medical Conditions Recognized as Being Aggravated by Exposure: None known

4. FIRST AID MEASURES

Ingestion: If swallowed, do NOT induce vomiting. Give victim two glasses of water. Call a physician immediately. Never give anything by mouth to an unconscious person..
Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention..
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Extremely Flammable per Flame Projection Test

5. FIRE FIGHTING MEASURES

Recommended Extinguishing Media:

Special Fire-Fighting Procedures:

Hazardous Products of Combustion:

Unusual Fire/Explosion Hazards:

Lower Explosive Limit:

Upper Explosive Limit:

Carbon Dioxide, Dry Chemicals, Foam.

Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Oxides of carbon, Silicon dioxide

Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

Not determined

Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Flush spill or leak area with water. Prevent from entering waterways or sewers. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst. Store in accordance with NFPA 30B for Level 3 Aerosols

Handling:

Avoid contact with skin and eyes. Use only in a well ventilated area. Spills may cause slippery floors. Proper footwear required. .

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Not normally required, but wearing safety glasses will minimize exposure. Recommended if handling large spills.

Skin:

Not normally required when using an aerosol.. Recommended if handling large spills..

Ventilation:

Mechanical ventilation

Respiratory Protection:

If handling large industrial or warehouse spills. wear NIOSH-approved respiratory protection..

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Clear liquid

Odor:

SOLVENT

Boiling Point:

>100°F

pH:

Does not apply

Solubility in Water:

Soluble

Specific Gravity:

0.8

VOC Content(Wt.%):

9.8% by weight

Vapor Pressure:

Not determined

Vapor Density (Air=1):

>1 (air = 1)

Evaporation Rate:

<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

WILL NOT OCCUR

Incompatibilities:

Strong oxidizers

Conditions to Avoid:

Keep away from heat, sparks and flame.

Hazardous Products of Combustion:

Oxides of carbon, Silicon dioxide

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:

Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash

Product name: NO TOUCH SERIOUSLY WET EXTREME
TIRE SHINE 15 OZ AE

Item No: NTSW15-6

13. DISPOSAL CONSIDERATIONS

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 500 ml)
Class or Division: Class 9
UN/NA Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity
Hazard Class: Class 2.1
UN Number: UN 1950

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 4, REACTIVITY 0

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: 05/16/2006
Revision Number: 1