

PROTECT YOUR WARRANTY

MASTER CYLINDERS



ONE VALIDATE DIAGNOSIS

- Key reasons for failure:
 - Seized piston
 - Leaking
 - Contaminated fluid

TWO BEFORE LEAVING AUTOZONE

- Compare the old part against the new part.
- Transfer needed parts from the old master cylinder if returning a core (reservoir and proportioning valve brass fitting).
- Be informed! Make sure you review all instructions included in the product box and available on Z-net for proper master cylinder bleeding. A reminder that some brake master cylinders must be mounted on the vehicle in order to bleed the brake system correctly.
- Register your master cylinder in our database for a hassle-free nationwide warranty.

THREE BEFORE INSTALLING

- ABS systems can be difficult to bleed. If any problems are encountered, don't hesitate to call technical support number listed below.

FOUR RECOMMENDED TOOLS

- A part specific bleeder kit is included with detailed instructions.
- Always make sure to use the correct brake fluid, do not substitute.
 - Consult the vehicles owners manual for specified brake fluid. Never re-use brake fluid. Use brake fluid from a new, sealed container.
- Haynes Repair Manual

FIVE TECHNICAL SUPPORT

Problems with installation?

Questions about how to do it right? Call our FREE tech hotline for live help from a certified expert technician:

1-866-787-5132

8:30am-4:30pm EST

Monday-Friday

