

PROTECT YOUR WARRANTY

FUEL PUMPS



ONE VALIDATE DIAGNOSIS

- It is important to check the entire system because *almost 50% of fuel pumps returned have nothing wrong with them.*
- Check the fuel pump relay and/or fuse.
- Check the fuel pump wire harness. Inspect the fuel pump connector on General Motors applications.
- Check the vehicle for the proper fuel pressure available in Z-net.

TWO BEFORE LEAVING AUTOZONE

- Compare the old part against the new part.
- Be smart! ALWAYS replace the fuel filter and strainer when replacing a fuel pump to validate your warranty.
- Save a trip! Take a fuel pump electrical connector “pigtail” to the store just in case.
- Be informed! Make sure you review all instructions included in the product box and available on Z-net.
- Register your fuel pump in our database for a hassle-free nationwide warranty.
- Check our FREE Loan-A-Tool® program for any tools needed.

THREE BEFORE INSTALLING

- ALWAYS disconnect the negative battery cable before you begin.
- IMPORTANT!! Clean the inside of the fuel tank.
- Replace tank, if needed.
- Inspect and repair questionable electrical connectors and wiring.
- Replace any leaking or questionable fuel lines, hoses and connections.
- **Warranty does not cover fuel pump failure due to rust, fuel contamination or vehicle electrical or connector issues.**

FOUR RECOMMENDED TOOLS

- Fuel Pump Replacement Kit #27160
- Fuel Line Disconnect Tool
- Fuel Pressure Gauge
- Haynes Repair Manual

FIVE TECHNICAL SUPPORT

Detailed installation information from Chiltons is available for many vehicles at www.autozone.com
Click the “Vehicle Repair Guides” link on the home page.

