

Instruction Sheet

Set #3-1117 (Gold Plated) Set #3.1118 (Chrome Plated)

These mounts are the "Tall & Narrow" style.

ENERGY
SUSPENSION

1131 VIA CALLEJON, SAN CLEMENTE, CA 92673

© 2004 Energy Suspension. All rights reserved.
May not be reproduced, in any form, or by any means,
without the written consent of Energy Suspension.


ENGINE MOUNT REMOVAL

1. Disconnect battery for safety reasons.
2. Support engine with jack under suitable location or under oil pan with wood block.
3. Remove bolts and nuts securing mounts to frame bracket.
4. Raise engine slightly with jack. (clearances between fan and shroud are slight, use caution when jacking.)
5. Remove bolts or nuts attaching mount to block.

ENGINE MOUNT INSTALLATION


(Note: due to unknown variation in aftermarket and factory engine mount bracket thickness, you must **check bolt threaded in length**. ENERGY SUSPENSION suggests that bolt threaded in length be no less than 1 1/2 times the bolt diameter.)

1. Position mount to block and install attaching hardware.
2. Lower engine into position and install bolt through frame brackets.
3. Remove jack.
4. Torque all nuts and bolts to factory specifications. (See notes "C" and "D")
5. Check fan and shroud for proper clearances.



- (A) Preload plate must be installed with the detent protrusion facing the engine block.
- (B) Bolt length must be at least 1 1/2 times diameter of bolt.
- (C) Torque to 25-35 FT. LBS.
- (D) Torque to 40-45 FT. LBS.

(Engine mount side view)



ENERGY SUSPENSION recommends replacing both right and left side engine mounts at the same time. Use a new lock nut at the frame